

L-A
Series
4 - 10 Hp

- ★ Air cooled
- ★ Single cylinder
- ★ Direct injected
- ★ Multiple PTO shaft options



Engine Model	Ratings (ISO 3046/1)		Bore x Stroke	Displacement	Dimensions			Dry Weight
	Max. Output, HP	Rated speed, rpm	mm X mm	cc	Length, mm	Width, mm	Height, mm	Lbs.
L40AE-D	4.2	3600	68 x 55	199	332.5	392.0	416.0	57
L40AE-DE	4.2	3600	68 x 55	199	332.5	392.0	416.0	68
L48AE-D	4.7	3600	70 x 55	211	332.5	392.0	416.0	57
L48AE-DE	4.7	3600	70 x 55	211	332.5	392.0	416.0	68
L60AE-D	6.0	3600	75 x 62	273	383.5	421.0	450.0	73
L60AE-DE	6.0	3600	75 x 62	273	383.5	421.0	450.0	84
L70AE-D	6.7	3600	78 x 62	296	383.5	421.0	450.0	73
L70AE-DE	6.7	3600	78 x 62	296	383.5	421.0	450.0	84
L90AE-D	9.0	3600	84 x 70	387	417.0	470.0	494.0	106
L90AE-DE	9.0	3600	84 x 70	387	417.0	470.0	494.0	117
L100AE-D	10.0	3600	86 x 70	406	417.0	470.0	494.0	106
L100AE-DE	10.0	3600	86 x 70	406	417.0	470.0	494.0	117

D = recoil start, DE spec. = electric start

Note: This engine series is not EPA certified.